

Shut-off Valves POM



CHARACTERISTICS

GENERAL

Constructional design	Shut-off valve
Application	Neutral gaseous or fluids
Product name	2-way Shut-off Valve
Product type	ASH-958P
Shaft thread	M22x1,5
Nominal diameter	8 - 10
Ambient temperature	-20 °C to +60 °C
Media temperature	-10 °C to +80 °C
Body material	POM blue
Seal material	NBR
Release ring	POM grey
Grip ring	Stainless steel 1.4310
Retaining ring	Nickel-plated brass

PNEUMATIC - HYDRAULIC

Nominal pressure	PN 10
Pressure range	Rough vacuum up to 10 bar
Medium	Gases or liquids which do not corrode the materials specified.

2-Way Shut-off Valve

Price group **34**

PN 10

Ambient-Temp. $T_{min} -20\text{ °C}$, $T_{max} +60\text{ °C}$
Med.-Temp. $T_{min} -10\text{ °C}$, $T_{max} +80\text{ °C}$

Plastic
POM

for tube OD	L	L1	L2	D1	D2	M	S	S1	S2	Weight in [g]	Type	Order number	Price
10	68	44,5	19,5	21	31,4	M22x1,5	8	27	19	55,0	ASH-958P-10	637779	o. r.
12	68	44,5	19,5	21	31,4	M22x1,5	8	27	19	57,4	ASH-958P-12	637780	o. r.

Illustration

